

Callaway Corvette C6 GT4

MANUFACTURER: Callaway Competition in Leingarten, Germany

COMPETITION CATEGORY: FIA GT4 Championship



General

- GT4 racing car (not road legal)
- Front mounted longitudinal V 8 engine with 6-speed rear trans-axle and rear wheel drive
- · Car has standard Corvette components unless otherwise stated
- · Optional passenger seat installation

Modifications

- · Interior removal, including door and rear window glass, except for dash and instrument panel
- · Installation of Polycarbonate rear and door windows
- · Installation of a complete eight-point safety roll cage (per FIA specifications)
- · Fire extinguishing system
- Driver protection
- · Quick release steering wheel and racing seat.
- · High performance racing braking system
- · Six-pot front calipers and four-pot rear calipers with vented rotors front and rear
- · Factory ABS system recalibrated for this application
- · Front brake cooling ducts
- · Up graded engine
- · Racing type dry sump-oiling system



- Lightweight flywheel/clutch package
- · Modified exhaust system with standard cats
- · Solid engine mounts
- · High performance air intake system
- · High performance full aluminum radiator
- · High-pressure water-cooling system
- · Oil/water heat exchange system
- · Power steering fluid cooler
- ATL FT3 100 liter fuel cell



Driveline Modifications

- · Reinforced Torque tube and driveshaft
- · Upgraded transmission and rearend cooling and oiling systems.
- · Short throw shifter with reinforced shift rod
- · Reinforced half shafts
- · Reinforced transaxle mounts
- High performance wheel bearings
- · Racing wheels with six-bolt lug system
- · GM ZR1 6-speed manual Gearbox with cooling close Ratio



Engine specs

- LS3 V8 engine mapped for 98 octane unleaded fuel
- Dry sump system with 3 stage external scavenge pump
- · Exhaust manifolds with straight through rear exit exhausts
- · Optional silencers available
- Power output 450 hp @ 6000 rpm (restricted to 390hp by FIA Air restrictor)
- Torque output 580 Nm @ 4900 rpm
- Max engine rpm 6200



Brakes

- · AP Racing 6-piston Front calipers
- · AP Racing 4-piston rear caliper
- 355mm vent front disc, 325mm vent rear disc
- · Front brake cooling ducts



Wheels

- OZ Racing cast magnesium alloyFront 18" rim 10" wide
- Rear 18" rim 10" wide



Tires

- Front Pirelli 265/645-18
- Rear Pirelli 305/680-18





- · Koenig Hans seat
- · Sabelt 6-point Hans harness
- · Adjustable steering wheel position
- · CAN interface to FIA Data logger
- Sabelt Electric Aluminum fire extinguisher system
- · Optional driver cooling AC
- · Optional passenger seat installation



Dimensions

- Length 4440mm
- Width 1850mm
- · Wheelbase 2670mm
- Dry weight 1400 Kg (Homologated weight)
- Fuel capacity 100 litres





Chassis

- · Standard C6 hydro formed steel chassis
- · Welded steel roll cage to FIA safety standards
- 100 litre FT 3 fuel cell with two quick fuelling valves
- · Pneumatic 4 point Air jack system
- · Polycarbonate rear window

Suspension

- · Moton dampers with bump and rebound adjustment
- · Eibach Race Springs
- · Adjustable Front and rear anti-roll bar





· Standard color is white, other colors on request



Contact

Compatibion

Callaway Competition GmbH

Liebigstr. 31 74211 Leingarten GERMANY

Phone: +49 7131 903110
Fax: +49 7131 9000 31
Email: info@callawaycars.de
Web: www.callawaycars.de